

BAQUACIL® AD™ Weekly Routine Pool Care

Maintaining your pool on the BAQUACIL system is even easier with BAQUACIL AD Automated Dosing System. Here's how it works.

Once a week, test your pool water with BAQUACIL Test Strips to make sure the levels of BAQUACIL AD Sanitizer and Algistat, pH and total alkalinity are within acceptable ranges.

If the BAQUACIL AD Sanitizer and Algistat level is below 30 ppm, top-up BAQUACIL AD Sanitizer and Algistat. (See Top-Up Dosage Chart below).

NOTE: Top-Up doses can vary from pool to pool. Never let the level fall below 30 ppm.

WEEKLY SUMMARY

1. Test the level of BAQUACIL AD Sanitizer and Algistat and top-up if level is at 30 ppm or below.
2. Test total alkalinity and adjust, if it is outside the 80–150 ppm range.
3. Test pH and adjust, if it is outside the 7.2–7.8 range.
4. Check Automated Dosing System for leaks, and product containers to ensure a sufficient level of product is available. If you need to install another product container, **see your Owner's Manual for complete instructions.**

NOTE: Thoroughly rinse product containers prior to disposal.

Top-Up Dosages for BAQUACIL AD Sanitizer and Algistat

IF LEVEL IS	0–14	Add 2 Top-Ups
	15–30	Add 1 Top-Up
	>30 ppm	No Top-Up Necessary

(TOP-UP DOSAGE IS 25.0 PPM.)

Based on your pool's volume, the chart below details the approximate product life of BAQUACIL AD products for the season.

Projected Package Life (Days)

BAQUACIL AD	Package Size (gallons)	Type of Container	Pool Volume (In thousands of gallons)					
			10	15	20	25	30	40
Sanitizer and Algistat	2.5	Initial	106 days	62 days	40 days	26 days	18 days	7 days
		Replacement	132 days	88 days	66 days	53 days	44 days	33 days
Oxidizer	4.5	Initial	80 days	46 days	29 days	18 days	11 days	3 days
		Replacement	103 days	69 days	51 days	41 days	34 days	26 days
Algicide 10	1.25	Initial	112 days	65 days	42 days	28 days	19 days	7 days
		Replacement	140 days	94 days	70 days	56 days	47 days	35 days

NOTE: Bold identifies pool volumes requiring an initial purchase of two packages.

NOTE: Newly converted pools on the BAQUACIL AD Pool Care System or problem pools should expect higher sanitizer consumption in the first year of operation. It is also recommended to test more frequently (i.e., every 5–7 days) to ensure a BAQUACIL AD Sanitizer and Algistat level of 30 ppm is present.

NOTE: When multiple oxidizer doses are needed, wear safety gloves and glasses to carefully remove the supply tubing from the BAQUACIL AD Algicide 10 product before initiating automatic oxidizer dose. Wipe off excess algicide on tube and place tube in a bucket.