

DryTec® and CCH® Dry Chlorinators

PRECAUTIONS FOR SAFE HANDLING AND STORAGE

WARNING: MAY BE FATAL IF SWALLOWED. AVOID BREATHING DUST OR FUMES. HARMFUL IF PRODUCT IS INHALED IN HIGH CONCENTRATIONS. CAUSES SKIN, EYE, DIGESTIVE TRACT, AND RESPIRATORY TRACT BURNS.

DO NOT TAKE INTERNALLY. AVOID INHALATION OF DUST AND FUMES. AVOID CONTACT WITH EYES, SKIN OR CLOTHING. UPON CONTACT WITH SKIN OR EYES, WASH OFF WITH WATER. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

STORAGE CONDITIONS: Keep product tightly sealed in original containers. Store product in a cool, dry, well-ventilated area. Store away from combustible or flammable products. Keep product packaging clean and free of all contamination, including, e.g., other pool treatment products, acids, organic materials, nitrogen-containing compounds, dry powder fire extinguishers (containing mono-ammonium phosphate), oxidizers, all corrosive liquids, flammable or combustible materials, etc.

DO NOT STORE AT TEMPERATURES ABOVE: 52 Deg.C (125 Deg.F) Storage above this temperature may result in rapid decomposition, evolution of chlorine gas and heat sufficient to ignite combustible products.

PRODUCT STABILITY AND COMPATIBILITY

SHELF LIFE LIMITATIONS: Shelf life (that is, the period of time before the product goes below stated label strength) is determined by storage time and temperatures. Do not store product at temperatures above 52 Deg.C (125 Deg.F). When stored under moderate temperature conditions, product will maintain stated label strength for approximately two years. Prolonged storage at 35 Deg.C (95 Deg.F) or above will significantly shorten the shelf life. Storage in a climate-controlled storage area or building is recommended in those areas where extremes of high temperature occur.

INCOMPATIBLE MATERIALS FOR PACKAGING: Product packaging must be clean and free of contamination by other materials, including, e.g., other pool treatment products, acids, organic materials, nitrogen-containing compounds, dry powder fire extinguishers (containing monoammonium phosphate), oxidizers, all corrosive liquids, flammable or combustible materials, etc.

INCOMPATIBLE MATERIALS FOR STORAGE OR TRANSPORT: Do not allow product to come in contact with other materials, including, e.g., other pool treatment products, acids, organic materials, nitrogen-containing compounds, dry powder fire extinguishers (containing mono-ammonium phosphate), oxidizers, all corrosive liquids, flammable or combustible materials, etc.

PERSONAL PROTECTIVE EQUIPMENT REQUIREMENTS

PERSONAL PROTECTION FOR ROUTINE USE OF PRODUCT:

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respirator if dusts are created.

VENTILATION: Use local exhaust ventilation to minimize dust and chlorine levels where industrial

use occurs. Otherwise, ensure good general ventilation.

SKIN AND EYE PROTECTIVE EQUIPMENT: Wear gloves, and safety glasses to avoid skin and eye contact. Where industrial use occurs, chemical goggles or full impermeable suit may be required.

EQUIPMENT SPECIFICATIONS (WHEN APPLICABLE):

RESPIRATOR TYPE: NIOSH/MSHA approved full face-piece respirator with chlorine cartridges and dust/mist prefilter.

PROTECTIVE CLOTHING TYPE: Neoprene

(This includes: gloves, boots, apron, protective suit)

FIRST AID

EYES: Immediately flush with large amounts of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Call a physician at once.

SKIN: Immediately flush with water for at least 15 minutes. Call a physician. If clothing comes in contact with the product, it should be removed immediately and laundered before reuse.

INGESTION: Immediately drink large quantities of water. DO NOT induce vomiting. Call a physician at once. DO NOT give anything by mouth if the person is unconscious or if having convulsions.

INHALATION: Remove victim to fresh air. Support respiration if needed. Call a physician.

SPILL AND LEAKAGE PROCEDURES

FOR ALL TRANSPORTATION ACCIDENTS, CALL CHEMTREC AT 800-424-9300.

REPORTABLE QUANTITY: 10 lbs. (as Calcium hypochlorite) Per 40 CFR 302.4

SPILL MITIGATION PROCEDURES: Hazardous concentrations in air may be found in local spill area and immediately downwind. Remove all sources of ignition. Stop source of spill as soon as possible and notify appropriate personnel.

AIR RELEASE: Vapors may be suppressed by the use of a water fog. All water utilized to assist in fume suppression, decontamination or fire suppression may be contaminated and must be contained before disposal and/or treatment.

WATER RELEASE: This material is heavier than water. This material is soluble in water. Monitor all exit water for available chlorine and pH. Advise local authorities of any contaminated water release.

LAND SPILL: Contact ACEAN® at 1-800-6546-911 immediately.

DANGER: All spills of this product should be treated as contaminated. Contaminated product may initiate a chemical reaction which may spontaneously ignite any combustible material present, resulting in a fire of great intensity. In case of a spill, separate all spilled product from packaging, debris and other material. Using a clean broom or shovel, place all spilled product into plastic bags, and place those bags into a clean, dry disposal container, properly marked and labeled. Disposal containers made of plastic or metal are recommended. Do not seal disposal containers

tightly. Immediately remove all product in disposal containers to an isolated area outdoors. Place all damaged packaging material in a disposal container of water to assure decontamination (i.e. removal of all product) before disposal. Place all undamaged packaging in a clean, dry container properly marked and labeled. Call ACEAN® for disposal procedures.

SPILL RESIDUES: Dispose of per guidelines under WASTE DISPOSAL.

This material may be neutralized for disposal; you are requested to contact ACEAN® at 800-6546-911 before beginning any such operation.

PERSONAL PROTECTION FOR EMERGENCY SPILL AND FIRE-FIGHTING SITUATIONS:
Response to this material requires the use of a full encapsulated suit and a NIOSH/MSHA approved positive pressure supplied air respirator.

WASTE DISPOSAL

If this product becomes a waste, it meets the criteria of a hazardous waste as defined under 40 CFR 261 and would have the following EPA hazardous waste number: D001.

If this product becomes a waste, it will be a hazardous waste which is subject to the Land Disposal Restrictions under 40 CFR 268 and must be managed accordingly.

As a hazardous solid waste, it must be disposed of in accordance with local, state, and federal regulations in a permitted hazardous waste treatment, storage and disposal facility by treatment.

CARE MUST BE TAKEN TO PREVENT ENVIRONMENTAL CONTAMINATION FROM THE USE OF THIS MATERIAL. THE USER OF THIS MATERIAL HAS THE RESPONSIBILITY TO DISPOSE OF UNUSED MATERIAL, RESIDUES AND CONTAINERS IN COMPLIANCE WITH ALL RELEVANT LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS REGARDING TREATMENT, STORAGE AND DISPOSAL FOR HAZARDOUS AND NONHAZARDOUS WASTES