

ICC-ES Evaluation Report**ESR-1721***

Reissued May 1, 2011

This report is subject to renewal May 1, 2013.www.icc-es.org | (800) 423-6587 | (562) 699-0543*A Subsidiary of the International Code Council®*

**DIVISION: 06 00 00—WOOD, PLASTICS AND
COMPOSITES**
Section: 06 05 73.13—Preservative Wood Treatment

REPORT HOLDER:

ARCH TREATMENT TECHNOLOGIES, INC.
5660 NEW NORTHSIDE DRIVE, SUITE 1100
ATLANTA, GEORGIA 30328
(678) 627-2000
www.wolmanizedwood.com
ptwinfo@wolmanizedwood.com

EVALUATION SUBJECT:

**WOLMANIZED® OUTDOOR® PRESERVATIVE-TREATED
WOOD**

ADDITIONAL LISTEES:

AMELIA LUMBER COMPANY
16951 LEIDIG STREET
AMELIA, VIRGINIA 23002

BESTWAY ENTERPRISES, INC.
3877 LUKER ROAD
CORTLAND, NEW YORK 13045

BORICUA WOOD PROCESSING
ROAD 865 KM 5.5
TOA BAJA, PUERTO RICO 00749

BURT LUMBER COMPANY
911 GREENSBORO ROAD
WASHINGTON, GEORGIA 30673

CABO ROJO TREATING PLANT CORPORATION
BARRIO BALLAJA, KM 1.1
CARRETERA 312-313, APARTADO 765
CABO ROJO, PUERTO RICO 00623

CONRAD FOREST PRODUCTS
68765 WILDWOOD ROAD
NORTH BEND, OREGON 97459

COX INDUSTRIES, INC.
860 CANNON BRIDGE ROAD
ORANGEBURG, SOUTH CAROLINA 29115

DANTZLER, INC.
7850 WEST BEAVER STREET
JACKSONVILLE, FLORIDA 32220

EAST TENNESSEE FOREST PRODUCTS
945 POTTERTOWN ROAD
MOSHEIM, TENNESSEE 37818

ESCUE WOOD PRESERVING, INC.
164 POST MILLWOOD ROAD
MILLWOOD, KENTUCKY 42762

EVERWOOD TREATMENT COMPANY
11349 HIGHWAY 31
SPANISH FORT, ALABAMA 36527

EXTERIOR WOOD, INC.
2685 INDEX STREET
WASHOUGAL, WASHINGTON 98671

FOLLEN WOOD PRESERVING COMPANY, INC.
1242 LANGLEY AVENUE
JACKSON, MISSISSIPPI 39204

GEORGIA-PACIFIC, LLC
19560 ALABAMA HIGHWAY 1272
ATHENS, ALABAMA 35614-6810

GREAT SOUTHERN ENTERPRISES
41815 HIGHWAY 195 SOUTH
HALEYVILLE, ALABAMA 35565

GREAT SOUTHERN WOOD PRESERVING
1100 HIGHWAY 431 NORTH
ABBEVILLE, ALABAMA 36310

H. M. STAUFFER & SONS, INC.
33 GLENOLA DRIVE
LEOLA, PENNSYLVANIA 17540

HATFIELD LUMBER COMPANY
139 POLK 29
HATFIELD, ARKANSAS 71945

KING TREATMENT
1364 MARCUM ROAD
ONEIDA, TENNESSEE 37841

LAVELLE COMPANY
115 31ST STREET SOUTH
FARGO, NORTH DAKOTA 58103

LITRELL BROTHERS LUMBER
20345 HIGHWAY 31 NORTH
VINEMONT, ALABAMA 35179

***Revised April 2012**

ICC-ES Evaluation Reports are not to be construed as representing aesthetics or any other attributes not specifically addressed, nor are they to be construed as an endorsement of the subject of the report or a recommendation for its use. There is no warranty by ICC Evaluation Service, LLC, express or implied, as to any finding or other matter in this report, or as to any product covered by the report.

LONG LIFE TREATED WOOD
8150 OLD RAILROAD ROAD
HEBRON, MARYLAND 21830

MADISON WOOD PRESERVERS, INC.
216 OAK PARK ROAD
MADISON, VIRGINIA 22727

McCREADY LUMBER COMPANY
4801 WURNO ROAD
PULASKI, VIRGINIA 24301

MID-STATES WOOD PRESERVERS
147 SHELBY ROAD
SIMSBORO, LOUISIANA 71275-0560

MIDWEST TIMBER, INC.
109 KRAUS ROAD
EDWARDSBURG, MICHIGAN 49112

NORTHEAST TREATERS, INC.
201 SPRINGFIELD ROAD
BELCHERTOWN, MASSACHUSETTS 01007-0802

PEACH STATE MANUFACTURING
4250 STACKS ROAD
COLLEGE PARK, GEORGIA 30349

PERMA-TREAT OF ILLINOIS
602 NORTH CARBON STREET
MARION, ILLINOIS 62959

PETERSON WOOD TREATING, INC.
2 RANDY JOHNSON STREET, INDUSTRIAL PARK
SUPERIOR, WISCONSIN 54880

PITTS LUMBER COMPANY
ROUTE 17
SALUDA, VIRGINIA 23149

PUERTO RICO WOOD TREATING
AVE. 65 DE INFANTERIA KM. 7.0
CAROLINA, PUERTO RICO 00929

ROBBINS PRESERVING & MANUFACTURING
1301 NORTH NEBRASKA AVENUE
TAMPA, FLORIDA 33612

SOUTH HOUSTON LUMBER
607 DUMONT STREET
SOUTH HOUSTON, TEXAS 77587

TIMBER WHOLESALERS
357 COUNTY ROAD 5 SW
WILLMAR, MINNESOTA 56201

TRI-STATE LUMBER, INC.
105 HOMAN ROAD
FULTON, MISSISSIPPI 38843

TRUGUARD, LLC
725 SOUTH 32ND STREET
WASHOUGAL, WASHINGTON 98671

UNITED WOOD PRESERVING, LLC
338 EAST WASHINGTON AVENUE, SUITE D
MUSCLE SHOALS, ALABAMA, 35661

UTAH WOOD PRESERVING COMPANY
1959 SOUTH 1100 WEST
WOODS CROSS, UTAH 84087

VARN WOOD PRODUCTS, LLC
107 NORTH BRANTLEY AVENUE
HOBOKEN, GEORGIA 31542

WOOD PRESERVERS, INC.
15939 HISTORY LAND HIGHWAY
WARSAW, VIRGINIA 22572

WOODTREATERS, INC.
224 SAWDUST ROAD
ROCKY POINT, NORTH CAROLINA 28457

1.0 EVALUATION SCOPE

Compliance with the following codes:

- 2012 and 2009 *International Building Code*[®] (IBC)
- 2012 and 2009 *International Residential Code*[®] (IRC)
- Other Codes (see Section 8.0)

Properties evaluated:

- Preservative-treated wood
- Decay resistance
- Termite resistance
- Corrosion
- Structural

2.0 USES

Wolmanized[®] Outdoor[®] preservative-treated wood is used for wood members that are required by the code to be protected against decay and termites.

3.0 DESCRIPTION

3.1 General:

Wolmanized[®] Outdoor[®] preservative-treated wood products are recognized for use in aboveground, ground contact, and freshwater contact applications and resist attack by fungal decay, and subterranean termites, including Formosan termites.

Wolman[®] E brand wood preservatives are produced by Arch Treatment Technologies, Inc., and are used by independently owned and operated wood preserving plants listed in Table 3 of this report to preservative-treat wood products in accordance with Wolmanized[®] Outdoor[®] Wood Standards and Wolman[®] E Quality Control Procedures.

3.2 Preservative System:

Wolman[®] E wood preservatives are based on copper combined with the organic fungicides tebuconazole and propiconazole. There are three formulations, copper azole Type B (CA-B), copper azole Type C (CA-C), and dispersed (micronized) copper azole Type C (μ CA-C or MCA-C). The CA-B formulation contains copper and tebuconazole. The CA-C formulations contains copper, propiconazole and tebuconazole.

3.3 Wood Species:

Wolman[®] E CA-B and CA-C wood preservatives are used to preservative-treat the following materials:

- a. Dimensional lumber and timbers of the following species consisting of primarily sapwood: southern pine, ponderosa pine, red pine, radiata pine, Scots pine, and Caribbean pine.
- b. Dimensional lumber and timbers of the following species consisting of primarily heartwood: Douglas fir, western hemlock, hem-fir.
- c. Lumber, of nominal size of 2-by-8 or less, for decking and speciality use of the species listed in (a) and (b), above.
- d. Southern pine and Douglas fir plywood.

- e. Round and sawn posts and building poles of southern pine, ponderosa pine, red pine, Douglas fir, hem-fir and western hemlock.
- f. Round timber piling, southern pine, ponderosa pine, and red pine.

Minimum preservative retention levels are provided in Table 1 of this evaluation report.

Wolman[®] E μ CA-C (MCA-C) wood preservative is used to preservative-treat the following materials:

- a. Dimensional lumber and timbers of the following species consisting of primarily sapwood: southern pine, ponderosa pine, red pine, radiata pine, and Caribbean pine.
- b. Dimensional lumber and timbers of the following species consisting of primarily heartwood: Western hemlock, hem-fir.
- c. Lumber of nominal size 2-by-8 or less, for decking and specialty use of the species listed in (a) and (b) above.
- d. Southern pine and Douglas-fir plywood.
- e. Round and sawn building posts and building poles of Southern pine, ponderosa pine, red pine, hem-fir and Western hemlock.
- f. Round timber piling, Southern pine, ponderosa pine and red pine.

Minimum preservative retention levels are provided in Table 1 of this evaluation report.

4.0 INSTALLATION

4.1 General:

Wolmanized[®] Outdoor[®] preservative-treated wood is installed as preservative-treated lumber, timbers and plywood in accordance with the requirements of the applicable code.

Arch Treatment Technologies' and industry published installation instructions for wood and pressure-treated wood and this report must be strictly adhered to, and a copy of the instructions must be available at all times on the jobsite during installation.

The instructions within this report govern if there are any conflicts between Arch Treatment Technologies' instructions and this report.

4.2 Applications:

Wolmanized[®] Outdoor[®] preservative-treated wood products are recognized for use in locations where wood is used and/or in locations required by the code to be fungal decay or termite resistant. The treated wood products are recognized for use in aboveground, ground contact and freshwater applications in all building types and occupancies where permitted by the applicable code. Typical applications are described in Table 2.

Locations requiring preservative-treated wood for fungal decay or termite resistance are described in Section 2304.11 of the IBC, and Sections R317 and R318 of the IRC.

4.3 Fasteners:

Fasteners used with Wolmanized[®] Outdoor[®] preservative-treated (CA-B, CA-C) wood products must be in accordance with Section 2304.9.5 of the IBC and Section R317.3 of the IRC. Aluminum fasteners and other aluminum building products (siding, flashing) must not be in direct contact with Wolmanized[®] Outdoor[®] preservative-treated (CA-B, CA-C) wood products.

Fasteners used with Wolmanized[®] Outdoor[®] preservative-treated μ CA-C (MCA-C) wood products must

be in accordance with Section 2304.9.5 of the IBC and Section R317.3 of the IRC. Aluminum fasteners and other aluminum building products (siding, flashing) may be used in direct contact with Wolmanized[®] Outdoor[®] preservative-treated μ CA-C (MCA-C) wood products.

4.4 Structural:

4.4.1 Duration of Load: The maximum load duration factor allowed for structural members pressure-treated with Wolman[®] E wood preservatives must be 1.6 in accordance with Section 2.3 of the American Forest & Paper Association (AF&PA) National Design Specification for Wood Construction (NDS).

4.4.2 Incising Factor: When the treated wood products have been incised, the reference design values must be multiplied by the incising factor, C_i , in accordance with Section 4.3.8 of the NDS.

5.0 CONDITIONS OF USE

The Wolmanized[®] Outdoor[®] preservative-treated wood described in this report complies with, or is a suitable alternative to what is specified in those codes listed in Section 1.0 of this report, subject to the following conditions:

- 5.1 Dimensional lumber designated for "Decking Use" must be a maximum of 2 inches (51 mm) thick and 8 inches (203 mm) wide.
- 5.2 Use of the preservative-treated wood is limited to the type of applications noted in Section 4.2 of this report.
- 5.3 Wolman[®] E wood preservatives are not recognized for use in treating LVL, OSB, or FRTW wood products.
- 5.4 Surface treatment of field cuts must be in accordance with the recommendations of Arch Treatment Technologies, Inc.
- 5.5 The Wolmanized[®] Outdoor[®] treated wood products are limited to the wood species noted in Section 3.3 with minimum retentions noted in Table 1.
- 5.6 The treatment process followed by each of the treaters recognized in this report must comply with this report, Arch Treatment Technologies Treatment Standards WOW-10 and WOD-10, and the Quality Control Manual for Treatment with Wolman[®] E Preservative.
- 5.7 Treatment of wood products is at the facilities of the treaters noted in Table 3, under a quality control program with inspections by Timber Products Inspection Inc. (AA-664 and AA-696) or Southern Pine Inspection Bureau (AA-680).

6.0 EVIDENCE SUBMITTED

- 6.1 Data in accordance with Appendix A, Copper-Azole Wood Preservative Treatment Systems (formerly AC143), of the ICC-ES Acceptance Criteria for Proprietary Wood Preservative Systems—Common Requirements for Treatment Process, Test Methods and Performance (AC326), dated February 2012.
- 6.2 Quality control documentation in accordance with Section 5.0 of AC326 with AWWA M22 compliance.

7.0 IDENTIFICATION

Wolmanized[®] Outdoor[®] preservative-treated lumber and plywood must be labeled or stamped with the name of the inspection agency (Timber Products Inspection Inc. or Southern Pine Inspection Bureau); the Wolmanized[®] Wood logo (see Figure 1); the production plant identification; the preservative designation CA-B, CA-C or μ CA-C (MCA-C); the intended end use; and the evaluation report number (ESR-1721). See Figure 1 for sample label.

8.0 OTHER CODES

In addition to the codes referenced in Section 1.0, the products described in this report were evaluated for compliance with the requirements of the following legacy codes and earlier editions of the International Codes:

- 2006 *International Building Code*[®] (2006 IBC)
- 2006 *International Residential Code*[®] (2006 IRC)
- 2003 *International Building Code*[®] (2003 IBC)
- 2003 *International Residential Code*[®] (2003 IRC)
- 2000 *International Building Code*[®] (2000 IBC)
- 2000 *International Residential Code*[®] (2000 IRC)

The Wolmanized[®] Outdoor[®] preservative-treated wood products described in this report comply with, or are suitable alternatives to what is specified in, the codes listed above, subject to the provisions of Sections 8.1 through 8.6.

8.1 Uses:

See Section 2.0.

8.2 Description:

See Section 3.0.

8.3 Installation:

See Section 4.0, except for the following modifications:

Locations requiring preservative-treated wood for decay or termite resistance are described in Section 2304.11 of the 2000, 2003 and 2006 IBC, Sections R323 and R324 of the 2000 IRC, and Sections R319 and R320 of the 2003 IRC and 2006 IRC.

Fasteners used with Wolmanized[®] Outdoor[®] preservative-treated wood products must be in accordance with Section 2304.9.5 of the 2000, 2003 and 2006 IBC, Section R323.3 of the 2000 IRC, and Section R319.3 of the 2003 IRC, Section R319.3 of the 2006 IRC, except that aluminum fasteners are also permitted in contact with Wolmanized[®] Outdoor[®] preservative-treated (μCA-C or MCA-C) wood products.

8.4 Conditions of Use:

See Section 5.0.

8.5 Evidence Submitted:

See Section 6.0.

8.6 Identification:

See Section 7.0.

TABLE 1—MINIMUM PRESERVATIVE RETENTION REQUIREMENTS FOR WOLMANIZED[®] OUTDOOR[®] PRESERVATIVE-TREATED WOOD PRODUCTS BY END USE

END USE	MINIMUM ACTIVES RETENTION ¹ pcf (kg/m ³)		
	CA-B ²	CA-C ³	μCA-C ³ (MCA-C)
Above ground - general use	0.10 (1.7)	0.060 (1.0)	0.050 (0.8)
Above ground - decking & specialties use			
• Species listed in Section 3.3 (primarily sapwood)	0.080 (1.3)	0.060 (1.0)	0.050 (0.8)
• Species listed in Section 3.3 (primarily heartwood)	0.21(3.3)	0.15 (2.4)	0.14 (2.2)
Ground contact - general use	0.21 (3.3)	0.15 (2.4)	0.14 (2.2)
Ground contact - heavy duty	0.31 (5.0)	0.25 (4.0) ⁴	0.23 (3.6)
Ground contact – wood foundation systems	0.31 (5.0)	0.25 (4.0) ⁴	0.23 (3.6)
Ground contact – extreme duty	0.41 (6.6)	0.35 (5.7) ⁴	0.33 (5.3)

¹Retention is expressed in pounds of preservative per cubic foot (kilograms per cubic meter) of preservative actives.

²Minimum retention of CA-B expressed as copper metal + tebuconazole.

³Minimum retention of CA-C and μCA-C (MCA-C) expressed as copper metal + tebuconazole + propiconazole.

⁴Retentions for these products differ from those listed in AWPA Standard U1.

TABLE 2—TYPICAL APPLICATIONS FOR WOLMANIZED[®] OUTDOOR[®] PRESERVATIVE-TREATED WOOD PRODUCTS

SERVICE CONDITIONS	AWPA USE CATEGORY ¹	TYPICAL APPLICATIONS
Above ground, interior dry uses	UC1	Interior construction, furnishings and millwork
Above ground, interior damp uses	UC2	Interior beams, timbers, flooring, millwork and sill plates
Above ground protected, exterior uses when coated and with rapid water runoff	UC3A	Coated millwork, siding, spindles, fascia and trim
Above ground exposed - general use	UC3B	Decking, rails, spindles, trim and fascia, framing, flooring, sill plates, trellises, gazebos, fencing
Ground contact - general use, ground or freshwater	UC4A	Deck support posts, fence posts, retaining walls
Ground contact - heavy duty, ground or freshwater	UC4B	Important components such as permanent wood foundations, sawn and round building poles
Ground contact extreme use, ground or freshwater uses—critical structural components	UC4C	Critical structural components such as land and freshwater foundation piling

¹μCA-C (MCA-C) has not been evaluated by and is not listed in the American Wood Protection Association (AWPA) Standards.


TABLE 3—WOOD PRESERVATIVE TREATMENT LOCATIONS

LISTEES	WOOD PRESERVATIVE TREATMENT LOCATIONS	TRADENAME ¹
Amelia Lumber Company	Amelia, VA	
Bestway Enterprises, Inc. [Treater Name Bestway of New York] Bestway of Gouverneur Bestway of New England Bestway of Pennsylvania Bestway South	Courtland, NY Gouverneur, NY S. Lancaster, MA Cresco, PA Stony Point, NC	
Boricua Wood Processing	Tora Baja, PR	
Burt Lumber Company	Washington, GA	
Cabo Rojo Treating Plant Corporation	Cabo Rojo, PR	
Conrad Forest Products	Arbuckle, CA North Bend, OR Rainier, OR	
Cox Industries, Inc. [Treater Name Cox Wood Preserving] Cove City Wood Preserving Structural Wood Preserving Cox of VA	Orangeburg, SC Cove City, NC Coleridge, NC Blackstone, VA	DuraPine®
Dantzler, Inc.	Jacksonville, FL	
East Tennessee Forest Products	Mosheim, TN	
Escue Wood Preserving	Millwood, KY	
Everwood Treatment Company	Spanish Fort, AL	
Exterior Wood, Inc.	Washougal, WA	Elite Decking™
Follen Wood Preserving, Inc.	Jackson, MS	
Georgia-Pacific, LLC	Athens, AL	
Great Southern Enterprises	Haleyville, AL	
Great Southern Wood Preserving Great Southern Wood – MS Great Southern Wood – MD Great Southern Wood – OH Great Southern Wood- VA	Brookhaven, MS Hagerstown, MD Fombell, PA Rocky Mount, VA	YellaWood® WeatherShield®
H. M. Stauffer & Sons, Inc.	Leola, PA	
Hatfield Lumber Company	Hatfield, AR	
King Treatment	Oneida, TN	
Lavelle Company	Fargo, ND	
Littrell Brothers Lumber	Vinemont, AL	
Long Life Treated Wood	Hebron, MD	
Madison Wood Preservers, Inc.	Madison, VA	MadWood™
McCready Lumber Company	Pulaski, VA	
Mid-States Wood Preservers	Simsboro, LA	
Midwest Timber	Edwardsburg, MI	
Northeast Treaters of Massachusetts Northeast Treaters of New York	Belchertown, MA Athens, NY	WeatherShield®
Peach State Manufacturing	College Park, GA	
Perma-Treat of Illinois	Marion, IL	
Peterson Wood Treating, Inc.	Superior, WI	
Pitts Lumber Company	Saluda, VA	
Puerto Rico Wood Treating Industries, Inc. (HQ) Puerto Rico Wood Treating Gulf Treating Southern Wood Treating	Carolina, PR Puerto Nuevo, PR Guayanilla, PR	
Robbins Preserving & Manufacturing	Tampa, FL Gainesville, GA Orlando, FL Rockwell, NC Thomaston, GA	NaturalMC™
South Houston Lumber	South Houston, TX	
Timber Wholesalers	Willmar, MN	
Tri-State Lumber Inc.	Fulton, MS	

TABLE 3—WOOD PRESERVATIVE TREATMENT LOCATIONS (Continued)

LISTEES	WOOD PRESERVATIVE TREATMENT LOCATIONS	TRADENAME ¹
TrueGuard, LLC (HQ) [Treater name Allweather Wood]	Loveland, CO	
United Wood Preserving, LLC	Muscle Shoals, AL	
Utah Wood Preserving	Woods Cross, UT	
Varn Wood Products, LLC	Hoboken, GA	
Wood Preservers, Inc.	Warsaw, VA	
Woodtreaters, Inc.	Rocky Point, NC	

¹All treatment locations may use the new Wolmanized® Outdoor® Wood trade name as noted in this report.

 <p>¹</p>	Preservative Designation ² End Use ³ ESR-1721 Quality Monitored by [Inspection Agency Name AA-###]
Treating Company Name And Plant Location(s) ⁴	

¹Other Trademarks may be used as permitted by Table 3.

²Refer to Table 1 for Minimum Retentions and Preservative Designations.

³Refer to Table 2 for Descriptions of End Uses; if the product is listed by AWPA, the Use Category designation may be included.

⁴Refer to Table 3 for Treating Company Names and Plant Locations.

FIGURE 1—SAMPLE PRODUCT LABEL