

NEW GENERATION



PRESSURE TREATED WOOD



**A new generation
wood preservative...
ideal for outdoor treated wood**

In TANALISED® E PRESSURE TREATED WOOD, we have a product that is strong enough to stand up to wood's natural enemies, yet is safe even in the most sensitive environment. In today's increasingly aware world, TANALISED® E PRESSURE TREATED WOOD is a natural and environmentally responsible choice.

Where can TANALISED® E pressure treated wood be used?

As with traditional treated wood, **TANALISED® E PRESSURE TREATED WOOD**, can be used in a wide range of applications.

H2: Interior above the Ground

Eg: roof trusses, purlins and battens, framing timber

H3: Exterior above the Ground

Eg: Decking joists, bearers and decking boards, outdoor furniture, balustrades and hand rails, walkways, fence battens, trellis, exterior cladding, beehives

H4: Exterior in the Ground

Eg: jungle gyms and play equipment, fencing posts, deck post, agricultural & vineyard posts, garden edging, pergolas, car ports, landscaping

H5: Exterior in Fresh Water

Eg: house piles, retaining walls, fresh water jetties and vineyards



Which other countries use TANALISED® E PRESSURE TREATED WOOD ?

TANALISED® E TREATED WOOD is accepted all over the world and has become the treated wood of choice, where restrictions (on close human contact applications) have been placed on more traditional forms of timber treatment. In Europe, Australasia, Asia and Africa it has been marketed under the TANALISED® E brand, whilst in the USA it has been marketed under the brand Wolmanized® Residential Outdoor Wood™, which has even been a recipient of the prestigious Good Housekeeping Seal, the ultimate accolade for consumer trust in a product.

IMPORTANT TIPS

The following important tips will assist in ensuring that TANALISED® E TREATED WOOD really lasts:

- Wherever the wood has been cut, drilled or notched, remember to reseal with a supplementary wood preservative product such as TANALISED® ENSEAL GREEN™.
- It is not recommended to place the cut ends of treated wood into ground contact..
- Painting or staining is recommended as soon as possible after construction for timber structures in outdoor situations, for example decking, to minimize weathering, splitting and cracking.
- Use hot dipped galvanized steel, or other metal fasteners of high corrosive resistance for all exterior timber applications.

You will not regret the small additional cost of taking these steps when you appreciate the long term benefits of durable outdoor structures built out of TANALISED® treated wood.



Important Safety Information



Do not burn treated wood off cuts or waste, as toxic fumes or residues may be produced.




Avoid inhaling the wood dust when machining or sanding.
Wear a filter mask if necessary.



Treated wood should not be used in applications such as countertops where it will come into contact with food.

25 year TANALISED® Lifetime Treatment Guarantee.

TANALISED® E PRESSURE TREATED SAWN TIMBER used in H2 (interior above-ground) and H3 (exterior above-ground) applications is supported by a 25 Year Treatment Guarantee against insect attack and wood decay.

- Timber must be treated by an approved TANALISED® Treater with **TANALITH® E** wood preservative in accordance with SANS 10005 – “Preservative Treatment of Timber”.
- The Treatment Guarantee is valid from date of purchase.
- The guarantee is transferable from one owner to the next within the 25 year period.
- Look for the  symbol to know that the timber is covered by the **TANALISED® Lifetime Treatment Guarantee**.

For more information and the Terms and Conditions ask your dealer for the **TANALISED® Lifetime Treatment Guarantee Brochure**, or visit our website on www.tanalised.com/sa



This certifies that Tanalised® treated wood is guaranteed against insect attack & wood decay as follows: ✓

TAN®C (CCA)(sawn)	50 years	
VACSOL® (TBTN-P)	25 years	
TAN®C Weatherwood® poles	25 years	
TAN®E (CuAz)(sawn)	25 years	✓

Dealer: **Summit Hardware**
No: 217 Date Purchased: 12.10.07
Signed: *J.J. Van Vuuren.*



Terms & conditions apply to this guarantee: refer to the **TANALISED® Lifetime Guarantee Brochure** or see www.tanalised.com/sa



Leaders in Wood Protection

Arch Wood Protection is the world leader in wood protection products with offices and operations on all six continents. Arch Wood Protection is well known for leading brands such as TANALITH®, ANTIBLU®, WOLMANIZED®, VACSOL®, WEATHERWOOD® and TANALISED®. The company has a track record of over 60 years servicing wood treatment plants in more than 50 countries. At the cutting edge of wood protection technology, Arch Wood Protection, prides itself as a highly skilled, service driven and customer focused organisation. Arch Wood Protection is a division of leading global Biocides company, Arch Chemicals, which has more than 3000 employees world wide.



**Arch
Wood
Protection**

www.tanalised.com/sa • Email: infos@archchemicals.com

16 Indus Road, Marburg • Port Shepstone

P O Box 54344, Marburg, 4252 • South Africa

Tel: +27 (0)39 682 6019 • Fax: +27 (0)39 682 6022

TANALISED®, TANALITH®, WEATHERWOOD® and VACSOL® are registered trade marks of ARCH TIMBER PROTECTION LTD (UK)

© Copyright subsists in this work. In terms of the Copyright Act, 1978, no part of this work may be reproduced in any form or by any means, electronic or mechanical, including, without limitation, photocopying, transmitting, recording or by any information storage and retrieval system, without the written permission of **Arch Wood Protection (SA) Pty Ltd**. Any unauthorised reproduction of this work will constitute copyright infringement and render the infringing party liable under both civil and criminal law.

Available at:

